



# SOLVIS

FOTONAPONSKI MODULI

## MODEL SV72 E



Premium kvaliteta



Raspon izlazne snage  
350-370 Wp



100% EL testing



Mehaničko  
opterećenje do 5400 Pa



Mala težina



Efikasnost  
modula do 19,07 %



Pozitivna tolerancija  
izlazne snage -0/+4,9 W



Proizvedeni u Hrvatskoj



IEC EN 61215  
IEC EN 61730-1, -2



IEC 62716 Ed.



IEC 61701



IEC TS 62804-1  
(PID otpornost)

### Jamstva:

10

godina, proizvođačko  
jamstvo

12

godina na 90% izlazne snage

25

godina na 80% izlazne snage



Vrijednosti parametara pri standardnim testnim uvjetima (STC)						
MODEL		SV72-350 E	SV72-355 E	SV72-360 E	SV72-365 E	SV72-370 E
Vršna snaga $P_{MPP}$	[W]	350	355	360	365	370
Dozvoljeno odstupanje	[W]	-0/+4,9				
Struja kratkog spoja $I_{SC}$	[A]	9,69	9,74	9,73	9,75	9,78
Napon praznog hoda $U_{OC}$	[V]	46,53	47,52	48,17	48,24	48,39
Nazivna struja $I_{MPP}$	[A]	9,16	9,21	9,13	9,20	9,30
Nazivni napon $U_{MPP}$	[V]	38,43	38,76	39,63	39,69	39,82
Dozvoljeno odstupanje napona i struje	[%]	± 3				
Učinkovitost modula	[%]	18,04	18,30	18,55	18,81	19,07

STC: 1000W/m<sup>2</sup> ozračenje, 25 °C temperatura ćelije, AM1,5 g optička masa zraka prema normi EN 60904-3  
 Prosječni pad učinkovitosti od 3,8 % pri insolaciji od 200 W/m<sup>2</sup> prema normi EN 60904-1

Vrijednosti parametara u točki NOCT						
MODEL		SV72-350 E	SV72-355 E	SV72-360 E	SV72-365 E	SV72-370 E
Vršna snaga $P_{MPP}$	[W]	256,2	259,8	263,3	265,8	269,5
Dozvoljeno odstupanje	[W]	-0/+4,9				
Struja kratkog spoja $I_{SC}$	[A]	7,78	7,82	7,81	7,83	7,85
Napon praznog hoda $U_{OC}$	[V]	43,0	43,7	44,3	44,4	44,5
Nazivna struja $I_{MPP}$	[A]	7,34	7,38	7,31	7,36	7,45
Nazivni napon $U_{MPP}$	[V]	34,9	35,2	36,0	36,1	36,2

NOCT: 800 W/m<sup>2</sup> ozračenje, 20 °C ambijentalna temperatura, 1 m/s brzina vjetra

MEHANIČKI PODACI		
Dimenzije (V x Š x D)	[mm]	1956 x 992 x 40
Masa	[kg]	22,5
Broj i vrsta ćelija		72 ćelije, monokristalični Si (PERC), 156 x 156 mm +/- 1mm
Enkapsulacija ćelija		Etilen-vinil acetat(EVA)
Staklo		3,2 mm kaljeno sunčano staklo
Pozadina		Višeslojna poliesterska folija
Okvir		Okvir od anodiziranog aluminija s dvostrukom stjenkom i otvorima za drenažu
Priključna kutija		IP67 s 3 Bypass diode
Priključni kablovi		Kabel 4mm <sup>2</sup> , dužine 1000mm

NAPOMENA: Za verzije modula SV72 E YYY, naponi i struja mogu varirati ovisno o odabranoj varijanti YYY (YYY = slovo(a), F za crni okvir, B za srebrni okvir i crnu poliestersku foliju, BC za crni okvir i crnu poliestersku foliju)

RADNI UVJETI		
Temperaturno područje	[°C]	-40 to +85
Maksimalni napon sustava	[V]	1000
Najveća dopuštena prekidna struja osigurača po nizu fotonaponskih modula		15A
Najveća dopuštena reverzna struja		15A
Maksimalno opterećenje		Ispitano do 5400 Pa (prednja strana 5400 Pa, stražnja strana 2400 Pa)
Otpornost na udar		Tuča promjera 25 mm pri brzini 23 m/s

TEMPERATURNJA SVOJSTVA		
Temperaturni koeficijent snage $P_{MPP}$	[%/K]	-0,42
Temperaturni koeficijent struje $I_{SC}$	[%/K]	0,05
Temperaturni koeficijent napona $U_{OC}$	[%/K]	-0,33

